



Latch Only Need to Prep Door For Pin 1" Hole x 1/2"

- Drawing is not a template, use as reference.
 Installation Instructions:
1. With door in closed position, screw backplate to face of door ensuring wider side is towards the jamb and the slot is at an angle. Be sure to prep. the face of your door by drilling 1" dia. x 1/2" deep hole to accommodate pin on back side of detachable lock bar.
 2. Engage detachable lock bar with backplate.
 3. Align padlock hole of detachable lock bar with eye. Mark Position and secure eye to jamb.
 4. To prolong life of product, painting the product and oiling on a regular basis is recommended.

ALL DIMENSIONS IN INCHES

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CROWN INDUSTRIAL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CROWN INDUSTRIAL IS PROHIBITED.	ID #: 0002480	STOCK PART #: 430
DESCRIPTION: Detachable Locking Bar Latch	MATERIAL:	
FINISH: Clear Zinc	# PCS: 1	REV:

DWG #: 0002479
 DRAWN:BCM 5/10/2017
 SHEET #1
 File: 0002479.idw

CROWN INDUSTRIAL
 So. San Francisco, Ca
 (650) 952-5150
 www.crown-industrial.com