
No. 524 Cane Bolts No's. 434 & 514 Spring Bolts

NO. 524 CANE BOTTOM BOLT



No. 524 Cane Bottom Bolt Construction: Steel. Bolt drops by gravity when handle is lifted out of socket. Keeper installed in wood or concrete floor. Application: For garage or warehouse doors.

Part Number	Dimensions	Projection From Door	Weight (Ea.)
524 P21	5/8" x 18"	1-5/16"	3-1/2 lbs.
524 P23	3/4" x 24"	1-7/16"	5 lbs.

Sec. Sec. Sec. Sec.

Finish: Clear Zinc, Black Zinc, or 304 Stainless Steel, w/ #4 Brushed Finish. Packaged: Boxed, with screws and keepers.

Additional Options:

0524PL Pad Lockable Keeper: Used to lock a cane bolt in the down position.

0524.00021SPD Cane Bolt with Hold Down Spring Assembly: Used in applications where a cane bolt needs to be held in the down position. *Also available for 524P23 cane bolt.

0524.00021SPU Cane Bolt w/ Hold Up Spring Assembly: Used in applications where a cane bolt needs to be held in the up position. *Also available for 524P23 cane bolt.

NO. 434 SPRING BOLTS AND KEEPER





No. 434p96 Bolt With No. 434p27 Keeper

No. 434p96 Bolt With No. 434p248 Keeper

No. 434 Spring Bolt with Keeper

Construction: Bolt and housing-malleable iron. Keeper, steel.

Application: For securing medium sized swing or slide-fold doors in the closed position. Available with two types of keepers to meet most door applications. Includes 36" steel chain with ring and clip. Suitable for stop side mounting on wood, composite of structural steel doors with 434 P248 and 434 P27 keepers. **Bolt size:** 4-3/4" wide x 6" long x 1-7/8" projection. When ordering, specify keeper desired.

Finish: Painted.

Packed: Boxed, less bolts.

Weight: 3-1/4 lbs per bolt; Keeper weight: 434 P248 (2 lbs.) 434 P27 (1 lb.)

NO. 514 SPRING BOLTS

No. 514 P36 Spring Bolt

Application: For securing small sized swing or slide-fold doors in the closed position. Includes two keepers for hinge side or stop side mounting and 36" steel chain with ring and clip.

Bolt Size: 3-1/2" wide x 9" long x 1-1/2" projection.

Construction: Steel.

Finish: Painted.

Packed: Boxed with wood screws. Weight: 2-3/4 lbs.



No. 514 P38 Spring Bolt

Application: For securing large sized swing or slide-fold doors in the closed position. Includes keeper for hinge side mounting only, and 60" steel chain with ring and clip.

Bolt Size: 4-1/4" wide x 9" long x 1-3/8" projection. Construction: Steel.

Finish: Painted. Packed: Boxed with wood screws. Weight: 6-1/2 lbs

Keeper Options (furnished at additional charge): No. 434p27 Keeper: For surface, stop side mounting. No. 514-FW Flush Keeper: For flush, stop side mounting.

